

## True diversity wireless receiver

**DA-901R System** is the 3rd generation true diversity system. It inherits the reliability in electronic circuit design and mechanical design of the legendary US-901. To cope with the development of the technology it features Remoset function. It synchronizes a transmitter with data of frequency, gain control, ID and so on by pushing a button. Scan function is also provided. RU-901G3 is for medium and large venues



### Specifications:

Frequency Preparation	PLL Synthesized Control
Carrier Frequency Range	614-650MHz
Frequency Setting	Remoset U Ultrasonic
Receiving Mode	True Diversity
Bandwidth	36MHz
S/N Ratio	> 105dB
T.H.D	<0.6% @ 1KHz
Sensitivity	-95dBm, S/N>80dB
CMRR	>80 dB
Audio Frequency Response	50Hz~18KHz±2dB
Antenna	BNC (F)
Antenna Bosster Power	DC12~15V/100mA
Display	LCD
Display Contents	Group, Channel, Frequency, Battery Status, Antenna A/B, AF Meter(LED BAR), RF Meter (LED BAR)
Controls	Power ON/OFF, Group, Channel, Frequency, Audio Level, Lock-on, Volume, Output Pad, Frequency Scan (ON/OFF)
Audio Output Level	Ref:±22.5KHz Dev@1KHz Toneφ6.3 Phone Jack:-10dBV XLR Jack:-4dBV(Line) · -24dBV(MIC)
AF Output Impedance	600Ω
Squelch	Pilot Tone & Noise Mute
Output Connector	Balanced XLR Socket x1 / Unbalanced φ6.3mm PHONE JACK x1
Power Supply	DC12~15V/500mA
Dimension	212.3mm(W)*38.3mm(H)* 144mm(D)

### Recommended accessories:

