



PoE Dante® ceiling speaker 6.25 inch

MDM-SP6

30/60W

MDM-SP6 is especially designed for PA systems based on Dante audio networks like our MusiCall Music & Message systems. It is suitable for installation into lightweight ceilings. The speaker is ideal for hotels, conference rooms, shoppingcenters, education, hospitals, retail stores, performing art centers, restaurants, airports, houses of worship, and board rooms. It features a Class-D amplifier, with a maximum digital input signal, the amplifier will provide 30W power.

MDM-SP6 is a Dante[™] audio network addressable and self-amplifed ceiling speaker system.

Power supply via POE+ (Power over Ethernet) or DC19V power supply, available at option. The speaker includes a Class-D amplifier which provides effective use of power.

The speaker is also compatible with AES67 which makes this speaker system to be flexible with other audio network systems. The network system is also Dante Domain Manager Ready.

MDM-SP6 has excellent dispersion, wide bandwidth and a smooth frequency response which makes this the top choice for today's overhead commercial applications.







Specifications:

Audio Input Dante Audio via Ethernet
Output Power 30W (amplifier)
Signal to Noise Ratio 105dB
RJ45 Interface 1x RJ45

Audio Compability Dante / Dante Domain

Manager / AES67

Route switching control Dante™ controller software

Power supply Power supply via POE+ [Power

over Ethernet, IEEE 802.3at2009] or DC19 V [4.74A] power

supply, available at option 1"swirl loaded dome tweeter

Tweeter 1"swirl loaded dome tweeter
Woofer Cone 6.25"aluminium cone bass/midrange

Rated Power 60W (speaker)
Rated impedance 8 Ohm (speaker)
Frequency Range 45Hz-20KHz
Sensitivity 91 dB
Hole Size Ø206mm

Dimensions Ø235*155mm [Diameter*depth]

Material ABS
Diameter of the Grille Ø232mm
Grille thickness 4mm



E-mail: info@dateq.nl Internet: www.dateq.nl Chamber of Commerce: 84615559 Bank: IBAN NL 41 RABO 0375260307 Bank swift: RABO NL2U TVA/VAT: NL 863282313B01

